


# DIFFERENTIAL PRESSURE TRANSMITTER PRE-28

- ✓ Overloads up to 413 bar total static pressure
- ✓ Accuracy 0,25%
- ✓ Any range from 0...16 mbar up to 0...25 bar
- ✓ Intrinsic safety certificate (ATEX, IECEx)
- ✓ Marine certificate – DNV, BV



Transmitter PRE-28  
Process connection **P type**  
Static pressure limit 40 bar

Transmitter PRE-28  
Version with **PN type** process connection.  
Static pressure limit 40 bar

Transmitter PRE-28 – version with **type C** and **CR**  
process connection to be mounted together with a  
valve manifold.  
Static pressure limit 250, 320 or 413 bar

## Application

The PRE-28 transmitter is applicable to the measurement of differential pressure of gases, vapours and liquids.

## Construction

The active element is a piezoresistance silicon sensor separated from the medium by separating diaphragm and a specially selected type of manometric fluid. The special desing of the active sensing element ensures withstanding the pressure surges and overloads of up to 413bar. The electronics is placed in a casing with a degree of protection IP65, IP67, depending on the type of electrical connection applied.

## Calibration

Potentiometers can be used to shift the zero position and the range by up to 10%, without altering the settings.

## Installation

The transmitter with P type process connection is not heavy, so it can be installed directly onto impulse lines. For fitting in any desired position on a Ø25 pipe the Aplisens mounting bracket (F125 mounting bracket, page IV/ 5) is recommended.

The version with C type process connection can be fitted directly to a 3- or 5-valve manifold. The factory-mounted transmitters with VM type valve manifold (page IV/ 2) are recommended. A transmitter without a valve manifold can be fitted in any position on a 2" pipe or on a wall using the C-2" mounting bracket (page IV/ 5).

When the special process connections are required for the measurement of levels and pressures (e.g. at food and chemical industries), the transmitter is provided with an Aplisens diaphragm seal. The differential pressure transmitters with diaphragm seals are described in detail in the further part of the catalogue.

## Technical data

<b>Materials:</b> Wetted parts:	type P process conn.	SS316L	<b>Hysteresis, repeatability</b>	0,05%
	type P(H) process conn.	SS316L or Hastelloy C276		<b>Thermal compensation range:</b>
Diaphragm	type C process conn.	SS316L	<b>Operating temperature range:</b>	-25+80°C
	Casing	SS316L, Hastelloy C276, Au	<b>Medium temperature range:</b>	-25+120°C (direct measurement)
		SS304		Over 120°C – measurement with use
		Option: SS316		an impulse line or diaphragm seals

**CAUTION:** the medium must not be allowed to freeze in the impulse line or close to the process connection of the transmitter.

## Technical data

Any measuring range 0...16 mbar ± 0...25 bar

	Measuring Range				
	25 mbar	100 mbar	1 bar	2 bar	25 bar
Overpressure Limit Static Pressure Limit (repeated, without hysteresis)	250 bar (option 413 bar) (40 bar for P type process connection)				
Accuracy	0,4%	0,4%	0,25%		
Long term stability	0,6% / year	0,2% / year	0,1% / year		
Thermal error	Typically 0,6% / 10°C max 1% / 10°C	Typically 0,3% / 10°C max 0,4% / 10°C	Typically 0,2% / 10°C max 0,3% / 10°C		
Zero shift error for static pressure*	0,1% / 10 bar				

\* Zeroing the transmitter in conditions of static pressure can eliminate this error.

<b>Output signal</b>	4...20 mA, two wire transmission 0...10 V, three wire transmission	<b>Load resistance</b> (for current output)	$R[\Omega] \leq \frac{U_{supl}[V] - 85V}{0,02A}$
		<b>Load resistance</b> (for supply output)	$R \geq 20k\Omega$

### Power supply

<b>output 4..20 mA:</b>	8...36 VDC (Ex 9...28 VDC) version TR: 10,5...36 VDC (Ex 12...28 VDC)
<b>output 0..10 V:</b>	13...30 VDC

**Error due to supply voltage changes** 0,005% (FSO) / V

## Ordering procedure

Model	Code	Description
PRE-28		Differential pressure transmitter
Versions, certificates	/Exia.....	II 1/2G Ex ia IIC T4/T5/T6 Ga/Gb II 1D Ex ia IIIC T110°C Da I M1 Ex ia I Ma
	/Exia (IECEX).....	IECEX Ex ia IIC T4/T5/T6 Ga/Gb Ex ia IIIC T110°C Da Ex ia I Ma
	/MR.....	Marine certificate – DNV, BV (not available in ALW and ALM version)
	/Tlen..... /TR.....	For oxygen service (sensor filled with Fluorolube fluid) Response time <30ms; only 4..20mA output
more than one option is available		
Measuring range	/...+... [required units]	Measuring range in relation to 4mA and 20mA (or 0 and 10V) output.
Analogue output signal	(without marking) /0+10V.....	4..20mA / power supply 10,5...36VDC (Ex 12...28VDC) 0...10VDC / power supply 13...30VDC
Measuring set range	/...+... [required units]	Calibrated range in relation to 4mA and 20mA (or 0V and 10V) output
Casing, electrical connection	/PD.....	Housing IP65 with DIN EN 175301-803 connector
	/PZ.....	304SS housing, IP66, packing gland M20x1,5
	/PZ316.....	316SS housing, IP66, packing gland M20x1,5
	/PM12.....	304SS housing, IP67 with thread M12x1 and connector with cable (3 m in standard)
	/PK12.....	304SS housing, IP67, cable electrical connection (3 m of cable in standard)
	/ALW *..... /ALM *.....	Aluminum housing, local display, IP65, DIN43650 connector Aluminum housing, local display, IP65, DIN43650 connector
Process connections	/C.....	Thread 1/4NPT F on the cover flanges cover flanges material SS316. Allows mounting with a valve manifold. Process connection of cover flange: M10 (option /C(7/16) - 7/16"UNF acc. to IEC 61518)
	/CR.....	C-type process connection rotated 90°
	/P.....	Thread M20x1,5 (male)
	/PN..... /code of diaphragm seal....	Thread 1/4"NPT (female) Diaphragm seal (see chapter of diaphragm seals) mounted on Hi side of transmitter, Lo side 1/4NPT Female
Material of diaphragms (refers only to C, CR, P, PN process connection)	(without marking).....	Diaphragms material SS316L
	/H.....	Diaphragms material Hastelloy C276 (all wetted parts in Hastelloy C276 on request)
	/Au.....	Gold plated diaphragms
Gasket (refers only to C, CR process connection)	(without marking).....	FPM Viton
	/NBR.....	NBR
	/PTFE.....	PTFE
Other specification	/C-2".....	Mounting bracket for 2" pipe (to C process conn.), mat. zincd steel
	/C-2"(SS).....	Mounting bracket for 2" pipe (to C process conn.), mat. Stainless Steel
	/C-2"B.....	Mounting bracket for 2" pipe (to C(7/16) process conn.), mat. zincd steel
	/C-2"B(SS).....	Mounting bracket for 2" pipe (to C(7/16) process conn.), mat. Stainless Steel
	/FI25.....	Mounting bracket for 1" pipe (to P process conn.), mat. Stainless Steel
	/RedSpaw P.....	Connector to weld impulse pipes dia. 12 and 14 mm, material 15HM(SO) or SS316(S). Only process connection P type
	/RedSpaw C.....	Connector to weld impulse pipes dia. 12 and 14 mm, material 15HM. Only process connection C type.
	/Red d/P 1/2".....	Adapter for differential pressure transmitters with C type process connection, output thread 1/2NPT F. Material SS316L
/.....	Description of required parameters	