

CGMT4



Micro - 4 sq.mm Ground/Earth Terminal Blocks.

These blocks are used for terminating Grounding/Earthing wires. They are green-yellow coded as per industry standards. CGMT4 is suitable for DIN 15 micro rail & can be used in conjunction with CMT4 Terminal Blocks.

TECHNICAL DATA

Tightening Torque	0.5 Nm
Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Yellow - Green
Type of Connection	Screw Clamp
Product Function	Earthing/Grounding
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 15 Rail
Screw Size	M3
Operated by	Screwdriver
Rated Surge Voltage	4 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	4 mm ²
Conductor Cross Section AWG/Kcmil min	22 mm ²
Conductor Cross Section AWG/Kcmil max	10 mm ²
Conductor Cross Section Stranded with Ferrule/Lug min	0.2 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	4 mm ²
2 Conductors with same Cross Section Stranded min	0.2 mm ²
2 Conductor with same Cross Section Stranded max	2.5 mm ²
Conductor Cross Section Solid min	0.2 mm ²
Conductor Cross Section Solid max	6 mm ²
2 Conductors with same Cross Section Stranded with TWIN Ferrule/Lug min	0.2 mm ²
2 Conductor with same Cross Section Stranded with TWIN Ferrule/Lug max	2.5 mm ²
Stripping Length	9 mm
Internal Cylindrical Gauge	A4

DIMENSIONS

Height with DIN 35 x 15 mm rail	30.7 mm
Length	27 mm
Width (Thickness)	6 mm

APPROVALS



ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CGMT4	4 sqmm Ground/Earth terminal block in Green-Yellow colour.	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA601-1M	Din 15 Rail slotted 1 meter	50
	CA509/K2	Marking Tag Blank suitable for CDL4U / CDL4U(I.S) / CTL2.5U / CTL2.5UH / CTL2.5UL / CTL2.5HUL / CTL2.5U(I.S) / CTL2.5U(I.S)D2 / CGMT4 / CSFL4U / CSFL4U(L) / CMT4 / CMB4 / ASF4 / ASF4(L) / CTS2.5(100
	SCS0.6/3.5	Electricians Screwdriver for slotted screws	10

Conductor Cross Section Stranded min.	0.2 mm ²	0.5 mm ²	0.5 mm ²
---------------------------------------	---------------------	---------------------	---------------------

RATINGS AS PER STANDARDS....

Conductor Cross Section Stranded max.	4 mm ²	4 mm ²	4 mm ²
Tightening Torque	0.5 Nm	0.5 Nm	0.5 Nm
Operating Temperature Range		-40 to +85 °C	