


CX6



6 sq.mm Spring Clamp Feed Through compact Terminal Blocks.

The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	41 A
Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Grey
Type of Connection	Spring Clamp
Product Function	Feed Through
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	6 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	8 AWG
Stripping Length	10 mm

DIMENSIONS

Height with DIN 35 x 15 mm rail	50.5 mm
Height with DIN 35 x 7.5 mm rail	43 mm
Length	62.1 mm
Width (Thickness)	8 mm

APPROVALS



ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CX6	6 sq.mm Feed Through Spring Clamp Compact Terminal Block in Grey colour	100
CX6BU	6 sq.mm Feed Through Spring Clamp Compact Terminal Block in Blue colour	100
CX6BK	6 sq.mm Feed Through Spring Clamp Compact Terminal Block in Black colour	100
CX6GN	6 sq.mm Feed Through Spring Clamp Compact Terminal Block in Green colour	100
CX6R	6 sq.mm Feed Through Spring Clamp Compact Terminal Block in Red colour	100
CX6Y	6 sq.mm Feed Through Spring Clamp Compact Terminal Block in Yellow colour	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50