


CXDL2.5



2.5 sq.mm Double Level Spring Clamp Terminal Blocks

CXDL2.5 is a double level Terminal Block used in high density wiring applications.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	24 A
Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Grey
Type of Connection	Spring Clamp
Product Function	Double Level
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	2.5 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	12 AWG

DIMENSIONS

Height with DIN 35 x 15 mm rail	57 mm
Height with DIN 35 x 7.5 mm rail	49.5 mm
Length	71 mm
Width (Thickness)	5 mm

APPROVALS



ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CXDL2.5	2.5 sq.mm 2 Level Compact Spring Clamp Terminal Block in Grey Colour	100
CXDL2.5BU	2.5 sq.mm 2 Level Compact Spring Clamp Terminal Block in Blue Colour	100
CXDL2.5BK	2.5 sq.mm 2 Level Compact Spring Clamp Terminal Block in Black Colour	100
CXDL2.5GN	2.5 sq.mm 2 Level Compact Spring Clamp Terminal Block in Green Colour	100
CXDL2.5R	2.5 sq.mm 2 Level Compact Spring Clamp Terminal Block in Red Colour	100
CXDL2.5Y	2.5 sq.mm 2 Level Compact Spring Clamp Terminal Block in Yellow Colour	100
CXDL2.5O	2.5 sq.mm 2 Level Compact Spring Clamp Terminal Block in Orange Colour	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50