

**CXF4**



**4 sq.mm Spring Clamp Fuse compact Terminal Blocks**

The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed.

**TECHNICAL DATA**

Weight	1000 gms
Rated Voltage	10 V
Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Grey
Type of Connection	Spring Clamp
Product Function	Single Level Fuse
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Fuse Fail Indication Voltage	8 KV
Rated Surge Voltage	8 KV
Pollution Degree	3

**CONNECTION DATA**

Conductor Cross Section Stranded min.	4 mm <sup>2</sup>
Conductor Cross Section Stranded max.- Output Side	24 AWG
Conductor Cross Section AWG/Kcmil min	10 AWG
Stripping Length	10 mm

**DIMENSIONS**

Height with DIN 35 x 15 mm rail	68.8 mm
Height with DIN 35 x 7.5 mm rail	61.3 mm
Length	65.4 mm
Width (Thickness)	6 mm

**APPROVALS**



**ORDERING INFORMATION**

CAT. NO.	DESCRIPTION	STD. PACK
CXF4	4 sq.mm Feed Through Spring Clamp Terminal Block in Grey colour	50
CXF4-1.0	4 sq.mm Compact Fuse Spring Clamp Terminal Block	50

**ACCESSORIES**

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50