


CXG2.5



2.5 sq.mm feed Through Ground/Earth Spring Clamp Terminal Blocks

These Terminal Blocks have specially designed alloy feet which help in achieving very low contact resistance and vibration proof grounding with the DIN rails. They green/yellow colour coded as industry standards.

TECHNICAL DATA

Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Green-Yellow
Type of Connection	Spring Clamp
Product Function	Earthing/Grounding
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Fuse Fail Indication Voltage	8 KV
Rated Surge Voltage	8 KV
Pollution Degree	3

DIMENSIONS

Height with DIN 32 rail	45.5 mm
Height with DIN 35 x 15 mm rail	38 mm
Height with DIN 35 x 7.5 mm rail	49.7 mm
Length	5 mm
Width (Thickness)	5 mm

APPROVALS



ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CXG2.5	2.5 sq.mm Feed Through Spring Clamp Grounding/Earthing Terminal Block	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50