

CXSG2.5



2.5 sq.mm feed Through Ground/Earth Spring Clamp Terminal Blocks

These Terminal Blocks have specially designed alloy feet which help in achieving very low contact resistance and vibration proof grounding with the DIN rails. They green/yellow colour coded as industry standards

TECHNICAL DATA

Housing Material	Polyamide
Comparative Tracking Index	1
Standard Colour	Green-yellow
Type of Connection	Spring Clamp
Product Function	Earthing/Grounding
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 35/DIN 35-15 Rail
Fuse Fail Indication Voltage	8 KV
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	2.5 mm ²
Conductor Cross Section Stranded max.- Output Side	24 mm ²
Conductor Cross Section AWG/Kcmil min	12 mm ²

DIMENSIONS

Height with DIN 32 rail	51 mm
Height with DIN 35 x 15 mm rail	43.5 mm
Height with DIN 35 x 7.5 mm rail	43 mm
Length	5 mm
Width (Thickness)	5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CXSG2.5	2.5 sq.mm Spring Clamp Grounding/Earthing Side Entry Terminal Block	100

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	CA509/K5	Blank Marking Tag	100