

| CYLINDER PROXIMITY SENSOR (RESIN BODY) | | |
|--|-------------------|--|
| SERIES | MODEL | DESCRIPTIONS |
| DM | DC VOLTAGE | |
| | DM-1202 | Cylinder Proximity Sensor : 2 mm |
| | DM-1204 | Cylinder Proximity Sensor : 4 mm |
| | DM-3010 | Cylinder Proximity Sensor : 10 mm |
| | DM-3015 | Cylinder Proximity Sensor : 15 mm |
| | AC VOLTAGE | |
| | DM-3010AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [10 |
| | DM-3015AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [15 |



DC Type DM-XXXX



AC Type DM-XXXXAO/AC

| CYLINDER PROXIMITY SENSOR (METAL BODY) | | |
|--|--|--|
| SERIES | MODEL | DESCRIPTIONS |
| TM | DC VOLTAGE (SHIELDED TYPE) | |
| | TM-0801 | Cylinder Proximity Sensor : 1 mm |
| | TM-1202 | Cylinder Proximity Sensor : 2 mm |
| | TM-1805 | Cylinder Proximity Sensor : 5 mm |
| | TM-3010 | Cylinder Proximity Sensor : 10 mm |
| | DC VOLTAGE (NON-SHIELDED TYPE) | |
| | TM-0802 | Cylinder Proximity Sensor : 2 mm |
| | TM-1204 | Cylinder Proximity Sensor : 4 mm |
| | TM-1808 | Cylinder Proximity Sensor : 8 mm |
| | TM-3015 | Cylinder Proximity Sensor : 15 mm |
| | AC VOLTAGE (SHIELDED TYPE) | |
| | TM-1202AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [2 mm |
| | TM-1805AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [5 mm |
| | TM-3010AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [10 |
| | AC VOLTAGE (NON-SHIELDED TYPE) | |
| | TM-1204AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [4 mm |
| TM-1808AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [8 mm | |
| TM-3015AO/AC | Cylinder Proximity Sensor / AC 2 Wire Normal Open or Normal Close - [15 | |



DC Type TM-XXXX (Shielded)



DC Type TM-XXXX (Non-Shielded)



AC Type TM-XXXXAO/AC (Shielded)



AC Type TM-XXXXAO/AC (Non-Shielded)

Features : Protection IP67 ; DC Type : NPN / PNP; Cable Length : 2 meter; Operating Red LED Available