

CURRENT CALIBRATOR

Model : CC-422

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC



The Art of Measurement

CURRENT CALIBRATOR

Model : CC-422

FEATURES

* Provide the quality and accuracy of handheld calibrator of precision current source.	* Portable instrument for calibrating process devices and measuring process signals.
* Adjustable 0-24 mA current source, 2 ranges.	* Current calibrator drives loads up to 500 ohms.

GENERAL SPECIFICATIONS

Display	LCD display, max. display counts 1999. 13 mm (0.5") digit size.	Operating Humidity	Less than 80% RH.
Function	mA Current source, 2 ranges. 0 - 19.99 mA x 0.01 mA. 0 - 24.0 mA x 0.1 mA.	Power Supply	006P DC 9V, MN1604/PP3 battery or equivalent. Alkaline type or heavy duty type.
Sampling Time	Approx. 0.4 second.	Dimension	185 x 78 x 38 mm (7.3 x 3.0 x 1.5 inch).
Operating Temperature &	0 °C to 50 °C (32 °F to 122 °F). Less than 80% RH.	Weight	265 g/0.58 LB (including battery).
		Accessories Included	Operational manual..... 1 PC. Cable with the alligator pairs (red & black), LN-TL421..... 1 PC.

ELECTRICAL SPECIFICATION (23 ± 5 °C)

Range	Display Resolution	Accuracy
0 - 19.99 mA	0.01 mA	± (0.25 % FS + 1 d)
0 - 24 mA	0.1 mA	± (0.5 % FS + 1 d)

* *FS* : full scale

* Appearance and specifications listed in this brochure are subject to change without notice.

0408-CC422