



VETRIX

INFRARED THERMOMETER

Model: VIR-600

- 12:1 D:S ratio
- Adjustable Emissivity 0.1~1.0
- $\pm 1.5^{\circ}\text{C}$ Temperature Measurement Accuracy
- User Defined Visual And Audio Alarm
- High Contrast EBTN Color Display
- MAX/MIN/AVG/DIFF/Hold Modes
- Ring Lasers
- Temperature Recording Up To 99 Groups
- Date/Time Display
- Time Scheduled Measurement




Scheduled measurement



Set a start time and interval, device will auto turn on at start time, perform a measurement, then turn off, and repeat the procedure once for every interval time. Interval range from 1 min to 96 hours, number of measurement and data storage can be up to 99 sets.

Ring laser



Unique patented display method that covers entire measured area, user will know exactly where the measurement is taking place.

VIR - 600	
Temperature range (°C)	-32°C ~ 600°C
Temperature range (°F)	-25.6°F ~ 1112°F
Accuracy (°C)	±1.5°C or ±1.5%
Accuracy (°F)	±3.0°F or ±1.5%
Repeatability	0.7(°C) or 0.7% (1.5(°F) or 0.7%)
D:S ratio	12:1 (95%)
Response time	≤250ms (95% of reading)
Emissivity	0.1~1.0 (adjustable, stores 5 sets of preset values)
Spectral response	8um~14um
Laser signal	Ring
Laser power	<1mW
Features	
Auto power off	✓
Low battery indication	✓
LCD display	Color EBTN
High/low temperature LED alarm	✓
High/low temperature audible alarm	✓
Data hold	✓
°C/°F selection	✓
MAX/MIN/AVG/DIF mode	✓
Lock measurement	✓
Data storage	99
Scheduled measurement	✓
Backlight	✓
Operating temperature	0°C~50°C (32°F~122°F)
Storage temperature	-20°C~60°C (-4°F~140°F)
Operating humidity	<90% RH (non-condensing)
Tripod mounting hole	✓
Power	9V battery
Display	30mm x 30mm
Product color	Red and grey
Product net weight	204g
Product size	160mm x 74mm x 48mm
Standard accessories	Battery, carrying bag
Standard individual packing	Gift box, blister, English manual
Standard quantity per carton	20pcs
Standard carton measurement	475mm x 350mm x 250mm
Standard carton gross weight	10.43kg



**No.35, Jalan OP 1/2, Pusat Perdagangan One Puchong, Off Jalan Puchong,
47160 Puchong, Selangor Darul Ehsan, Malaysia.**

T : +603-8071 6322 | F : +603-8071 6822 | E : info@dpstar.com.my