

Industrial Dehumidifier



ecoFD-A65L



ecoFD-A125L



ecoFD-A155L



Features

- » Humidity entire computer display & control functions
- » Timer switch function, high-low speed
- » Automatically stop the water, sound and light alarm
- » Power & memory
- » Automatic defrost, continuous drainage
- » Universal mobile wheel
- » R410A environmentally friendly refrigerant
- » With remote control can be remotely controlled



Protection
Circuit



Precise
Control



Intelligent
Defrost



Autodiagnosis



Automatic
Protection



MODEL	ecoFD-A65L	ecoFD-A125L	ecoFD-A155L
Dehumidifying Capacity L/day (@ 30 deg. C, 80%RH)	65	125	155
Power Supply	220-240V 50Hz	220-240V 50Hz	220-240V 50Hz
Rated Power (W)	1000	1500	1940
Rated Current (A)	4.5	7	8.4
Airflow (cmh)	480	1000	1600
Working Temp. Condition (deg. C)	5-35	5-35	5-35
Refrigerant	R410A	R410A	R410A
Water Tank Capacity	10liters	-	-
Unit Dimension (WxDxH mm)	405x268x632	300x550x760	608x601x966
Packing Dimension (WxDxH mm)	445x320x666	330x580x815	745x650x1150
Net Weight (kg)	45	55	90
Gross Weight (kg)	48	104	95
Recommended Applicable Area m ²	40	60	70



No.35, Jalan OP 1/2, Pusat Perdagangan One Puchong, Off Jalan Puchong, 47160 Puchong, Selangor Darul Ehsan, Malaysia.

+603-8071 6322

info@dpstar.com.my

+603-8071 6822

www.dpstar.com.my

