

- Auto Range
- Four Channel Input
- Four Channel Display
- LED Back Light
- With Window Software
- RS-232 Interface
- 16,000 Records Data Logger each channel

THERMOMETER

304/309



- Auto Range
- Four Channel Input
- Four Channel Display
- LED Back Light
- With Window Software (309)
- RS-232 Interface
- 16,000 Records Data Logger each channel (309)
- Auto Power Off
- HOLD Function
- MAX/MIN Function
- Resolution 0.1℃/0.1℃
- Low Battery Indication

Four Channel Display



T1-T2 Display



SPECIFICATIONS

Measurement Range: -200°C~1370°C

-328°F~2498°F

Accuracy: -200°C~1370°C.....±0.3%rdg+1°C

-328°F~2498°F.....±0.3%rdg+2°F

Input Protection: 60V DC or 24Vrms AC Maximum

Battery Type: 9V Battery

Operating Condition: 0° C to 50° C (<80%RH) Storage Condition: -20° C to 60° C (<70%RH)

Dimensions: 184mm×64mm×30mm

Weight: Approx.220g

Accessories: Battery, Operation Manual, Carrying Case

Temperature Probe TP-K01×2Pcs RS-232 Cable (309), Software (309)

LED Back Light

CENTER 304 TYPE K

Four Channel Input

RS-232 Software



Option Accessories



*The specification and other informatiin in this catalogue are subject to change without prior notice.