# Data Logger HYGRO THERMOMETER

318

CE

# FEATURES

- Interchangeable Digital Probes.
- Thermistor Sensor For Temperature Measurement, Fast Response Time
- Dew Point Measurement.
- Extending Cable Available.



CENTER 318 DA

## Data Logger HYGRO THERMOMETER



#### FEATURES

- Interchangeable Digital Probes.
- Thermistor Sensor For Temperature Measurement, Fast Response Time
- Dual Display.
- Dew Point Measurement.
- PC Interface.
- 16,000 Records Data Logger.
- Auto Shut Off For Battery Saving.
- Extending Cable Available.
- Tilt Stand.

#### **SPECIFICATIONS**

#### Sensor:

Electronic capacitance polymer film sensor/NTC **Measurement Range:** 

Temperature:  $-20^{\circ}$ C~ $60^{\circ}$ C,  $-4^{\circ}$ F~ $140^{\circ}$ F Humidity:  $0^{\circ}$ RH~ $100^{\circ}$ RH

**Resolution:** 0.1°C/0.1°F/0.1%RH

#### Accuracy:

Temperature:  $\pm 0.8^{\circ}$ C,  $\pm 1.5^{\circ}$ F Humidity:  $\pm 2.0^{\circ}$ RH

Response Time: (@t90; in slowly moving air)

Humidity: 60 sec.

Temperature: 10sec.

**Display:** LCD, 2 lines.

#### Parameters Displayed:

Relative humidity, temperature and dew point.

Battery Type: 9V battery

Battery Lifetime: Approx. 80 hours Dimensions:

Dimensions:

Meter:  $185(L) \times 65(W) \times 36(H)$ mm Probe:  $94(L) \times 15$ mm Dia

Weight: Approx. 285g

**Vergiit.** Approx. 2000

### Accessories:

9V Battery, Instruction Manual, Windows software, USB Cable, RS-232 Cable(Option), Carry Case, AC Adapter(Option).







Humidity Cell (OPTIONAL)

\*The specification and other informatiin in this catalogue are subject to change without prior notice.