Wireless Four Channel Input DATA LOGGER THERMOMETER



T2

T3

T4

SPECIFICATIONS

- T1-T2 function
- Temperature alarm function
- Data Hold function
- Adjustable auto power off time setting
- Fast response with high accuracy
- Measures K, J, E, T, N, R, S type thermocouples
- Min/Max/Avg recording of all channels
- USB interface, PC software included
- Datalogging up to 32,000 points each channel
- Large backlit LCD shows all channels on display
- Recall function to instantly read-out up to 100 sets manually saved data
- Bluetooth capability



LIGATORS () Bandhing for blottooth device



APP available for iOS & Android system

SPECIFICATIONS

Measurement Range: -200°C~1370°C; -328°F~2498°F Accuracy: ±0.1%rdg+0.7°C; ±0.1%rdg+1.4°F Resolution: 0.1°C; 0.1°F Input Protection: 30Vrms Maximum Battery Type: 1.5V AAA size Battery x 4 pcs Operating Condition: 0°C to 50°C(<90%RH) Storage Condition: -20°C to 60°C(<75%RH) Dimensions: 187 x 75 x 29 (mm) Accessories: User's manual, micro USB cable, battery, Windows software, carrying case, K type bead probe x 2 pcs,

R

carrying case, K type bead probe x

BT-01 Bluetooth adapter.







BT-01 BLUETOOTH ADAPTER



(Dimensions: 36x24x6.5 mm)



*The specification and other informatiin in this catalogue are subject to change without prior notice.